IN THE CLAIMS:

- 1 1. (Currently Amended) Α thermal barrier coating 2 comprising a layer of rare-earth element phosphate said layer having a 3 thickness greater than about 20 micrometers, a thermal conductivity less 4 than about 2 W/mK and disposed on an exterior surface of a substrate one 5 of a ceramic substrate and a metallic substrate selected from the group 6 consisting of a nickel-based superalloy, an iron-based superalloy and a 7 cobalt-based superalloy so as to thermally protect the substrate.
- 1 2. (Original Claim) The thermal barrier coating according 2 to Claim 1 further comprising a monazite or xenotime crystal structure.
- 3. (Original Claim) The thermal barrier coating according to Claim 1, wherein the ratio between rare-earth element and phosphate is about 1:1.
- 4. (Previously Presented) The thermal barrier coating according to Claim 1, wherein the layer has a thickness between about 20 and 500 micrometers.
- 5. (Original Claim) The thermal barrier coating according to Claim 1 deposited on a substrate having a temperature between 600°C and 1100°C.

- 1 6. (Original Claim) The thermal barrier coating according
- 2 to Claim 5 deposited on a substrate having a temperature between 750°C
- 3 and 950°C.
- 7. (Original Claim) The thermal barrier coating according
- 2 to Claim 1 formed by a process selected from the group consisting of
- 3 chemical vapor deposition, physical vapor deposition, electron beam
- 4 evaporation, pulsed electron beam evaporation, laser ablation, and plasma
- 5 spraying.
- 1 8. (Original Claim) The thermal barrier coating according
- 2 to Claim 7 using single or multiple sources of materials selected from the
- 3 group consisting of rare-earth phosphates and mixtures of rare-earth
- 4 precursors with phosphorous precursors.
- 1 9. (Original Claim) The thermal barrier coating according
- 2 to Claim 1 formed with a columnar microstructure.
- 1 10. (Original Claim) The thermal barrier coating according
- 2 to Claim 1 formed with a porous microstructure.
- 1 11. (Original Claim) The thermal barrier coating according
- 2 to Claim 1, wherein the phosphate is lanthanum phosphate.

12-13 (Cancelled)

- 1 14. (Currently Amended) The thermal barrier coating 2 according to Claim 13 1 further comprising a layer of aluminum phosphate 3 disposed between the layer of rare-earth element phosphate and the metallic substrate.
- 1 15. (Currently Amended) The thermal barrier coating 2 according to Claim 13 1 further comprising a layer of alumina between the 3 metallic substrate and said rare-earth element phosphate.
- 1 16. (Original Claim) The thermal barrier coating according 2 to Claim 15 further comprising a region of rare-earth aluminate between the 3 alumina and said rare-earth element phosphate.
- 1 17. (Original Claim) The thermal barrier coating according to Claim 1 comprising a mixture of lanthanum phosphate, cerium phosphate and neodymium phosphate.
- 1 (Currently Amended) Α thermal barrier coating 2 comprising a layer of lanthanum phosphate said layer having a thickness 3 greater than about 20 micrometer and disposed on an exterior surface of a 4 substrate one of a ceramic substrate and a metallic substrate selected from 5 the group consisting of a nickel-based superalloy, an iron-based superalloy 6 and a cobalt-based superalloy so as to thermally protect the substrate.
- 19. (Original Claim) The thermal barrier coating according
 to Claim 18 further comprising a monazite crystal structure.

- 1 20. (Original Claim) The thermal barrier coating according
- 2 to Claim 18, wherein the ratio between lanthanum and phosphate is about
- 3 1:1.
- 1 21. (Currently Amended) The thermal barrier coating
- 2 according to Claim 18, wherein the layer has a thickness between about 20
- 3 and 500 micrometers.
- 1 22. (Original Claim) The thermal barrier coating according
- 2 to Claim 18 deposited on a substrate having a temperature between 600°C
- 3 and 1100°C.
- 1 23. (Original Claim) The thermal barrier coating according
- 2 to Claim 22 deposited on a substrate having a temperature between 750°C
- 3 and 950°C.
- 1 24. (Original Claim) The thermal barrier coating according
- 2 to Claim 18 formed by a process selected from the group consisting of
- 3 chemical vapor deposition, physical vapor deposition, electron beam
- 4 evaporation, pulsed electron beam evaporation, laser ablation, and plasma
- 5 spraying.
- 6 25. (Original Claim) The thermal barrier coating according
- 7 to Claim 24 using single or multiple sources of materials selected from the
- 8 group consisting of rare-earth phosphates and mixtures of rare-earth
- 9 precursors with phosphorous precursors.

- 1 26. (Original Claim) The thermal barrier coating according
- 2 to Claim 18 formed with a columnar microstructure.
- 1 27. (Original Claim) The thermal barrier coating according
- 2 to Claim 18 formed with a porous microstructure.

28.-29. (Cancelled)

- 1 30. (Currently Amended) The thermal barrier coating
- 2 according to Claim 29 18 further comprising a layer of aluminum phosphate
- 3 disposed between the layer of lanthanum phosphate and the metallic
- 4 substrate.
- 1 31. v(Original Claim) The thermal barrier coating according
- 2 to Claim 18 further comprising a layer of alumina between the metallic
- 3 substrate and the lanthanum phosphate.
- 1 32. (Original Claim) The thermal barrier coating according
- 2 to Claim 31 further comprising a region of lanthanum aluminate between the
- 3 alumina and the lanthanum phosphate.
- 1 33. (Original Claim) The thermal barrier coating according
- 2 to Claim 18 comprising a mixture of lanthanum phosphate, cerium
- 3 phosphate and neodymium phosphate.

- 1 34. (Currently Amended) Α thermal barrier coating 2 comprising a layer of a mixture of rare-earth element phosphates and 3 refractory oxides said layer having a thickness greater than about 20 4 micrometers, a thermal conductivity less than about 2 W/mK and disposed 5 on an exterior surface of a substrate one of a ceramic substrate and a 6 metallic substrate selected from the group consisting of a nickel-based superalloy, an iron-based superalloy and a cobalt-based superalloy so as to 7 8 thermally protect the substrate.
- 1 35. (Previously Presented) The thermal barrier coating 2 according to Claim 34, wherein the layer has a thickness between about 20 and 500 micrometers.
- 1 36. (Original Claim) The thermal barrier coating according 2 to Claim 34 deposited on a substrate having a temperature between 600°C and 1100°C.
- 1 37. (Original Claim) The thermal barrier coating according 2 to Claim 34 formed by a process selected from the group consisting of 3 chemical vapor deposition, physical vapor deposition, electron beam 4 evaporation, pulsed electron beam evaporation, laser ablation, and plasma 5 spraying.
- 6 38. (Original Claim) The thermal barrier coating according 7 to Claim 34 formed with a columnar microstructure.

- 1 39. (Original Claim) The thermal barrier coating according 2 to Claim 34 formed with a porous microstructure.
 - 40.-41. (Cancelled)
- 1 42. (Currently Amended) The thermal barrier coating 2 according to Claim 41 34 further comprising a layer of aluminum phosphate 3 disposed between the mixture and the metallic substrate.
- 1 43. (Original Claim) The thermal barrier coating according 2 to Claim 34 further comprising a layer of alumina between the metallic 3 substrate and the mixture.
- 1 44. (New) The thermal barrier coating according to Claim 43 2 further comprising a region of rare-earth aluminate between the alumina and 3 said rare-earth element phosphate.